ONLINE CERTIFICATIONS DIRECTORY

BBCV2.MH48852 Lithium Batteries - Component

Page Bottom

Lithium Batteries - Component

See General Information for Lithium Batteries - Component

MH48852

Model No.	Secondary Type ^[d]	Max Charging Current (Ic), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]	
FST18650-2000mAh	Lithium ion (Cylindrical)	2000	4.2	1	
FST18650-2200mAh	Lithium ion (Cylindrical)	2200	4.25	1	
FST18650-2400MAH	Lithium ion (Cylindrical)	2400	4.2	1	
FST18650-2500mAh	Lithium ion (Cylindrical)	2500	4.25	1	
FST18650-2600mAh	Lithium ion (Cylindrical)	2600	4.25	1	
FST18650-3000mAh	Lithium ion (Cylindrical)	3000	4.4	1	
FST18650BE-2000mAh	Lithium ion (Cylindrical)	2000	4.25	1	
FST18650NB-2200mAh	Lithium ion (Cylindrical)	2200	4.25	1	

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 Complies with all single-cell tests
- 2 Complies with all single-cell tests except the impact test
- 3 Complies with all single-cell tests except the projectile test
- 4 Complies with all single-cell tests except the crush test

Marking:	Company name or tradename	"FST"	, Recognized Component Mark,	N	on the cell	or smallest	shipping packag	e containing the
cell.								

Last Updated on 2016-07-12

Questions?

Print this page

Terms of Use

Page Top

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".