



BBCV2.MH48250 Lithium Batteries - Component

[Page Bottom](#)

Lithium Batteries - Component

[See General Information for Lithium Batteries - Component](#)

MH48250

Model No.	Secondary Type ^[d]	Max Charging Current (I _c), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]
103133	Lithium ion (Pouch)	900	4.2	1
1032100	Lithium ion (Pouch)	950	4.2	1
125374	(Pouch)	2500	4.2	1
175983	(Pouch)	5000	4.2	1
2575130	(Pouch)	3000	4.2	1
2765148	Lithium ion (Pouch)	3000	4.2	1
2782154	Lithium ion (Pouch)	3800	4.2	1
28120105	Lithium ion (Pouch)	4000	4.2	1
2870150		3500	4.2	1
2984180	Lithium ion (Pouch)	5000	4.2	1
30100122	Lithium ion (Pouch)	4200	4.2	1
30107108	Lithium ion (Pouch)	4600	4.2	1
3055135	Lithium ion (Pouch)	2200	4.2	1
3055146	Lithium ion (Pouch)	2650	4.2	1
3065165	Lithium ion (Pouch)	3800	4.2	1
3065190	Lithium ion (Pouch)	4000	4.2	1
3070100	Lithium ion (Pouch)	2400	4.2	1
3075145	Lithium ion (Pouch)	4000	4.2	1
3076142	Lithium ion (Pouch)	3600	4.2	1
3098152	Lithium ion (Pouch)	5000	4.2	1
32105209	Lithium ion (Pouch)	4100	4.2	1
3270105	Lithium ion (Pouch)	3000	4.2	1
3270110	Lithium ion (Pouch)	3000	4.2	1
329086	Lithium ion (Pouch)	2700	4.2	1
33100109	(Pouch)	4000	4.2	1
33111125	(Pouch)	5000	4.2	1
3365105	Lithium ion (Pouch)	2800	4.2	1
3370105	(Pouch)	2700	4.2	1
3371101	Lithium ion (Pouch)	2700	4.2	1
3380102	Lithium ion (Pouch)	2750	4.2	1
3393104	Lithium ion (Pouch)	4000	4.2	1
3552142	Lithium ion (Pouch)	3500	4.2	1

3565144	Lithium ion (Pouch)	3600	4.2	1
3570100A	Lithium ion (Pouch)	2500	4.2	1
3570100B	Lithium ion (Pouch)	2800	4.2	1
3570105	Lithium ion (Pouch)	3000	4.2	1
3572164	Lithium ion (Pouch)	5300	4.2	1
3577156	Lithium ion (Pouch)	5000	4.2	1
3585164	Lithium ion (Pouch)	5800	4.2	1
3689192	Lithium ion (Pouch)	3650	4.2	1
3695192	Lithium ion (Pouch)	3900	4.2	1
387594	Lithium ion (Pouch)	3300	4.2	1
40100160	(Pouch)	3600	4.2	1
40109140	(Pouch)	3500	4.2	1
40120105	(Pouch)	6200	4.2	1
4070100	(Pouch)	3000	4.2	1
4073112	Lithium ion (Pouch)	4000	4.2	1
454770	Lithium ion (Pouch)	1000	4.2	1
458097	(Pouch)	4000	4.2	1
504045	Lithium ion (Pouch)	950	4.2	1
505093	Lithium ion (Pouch)	1500	4.2	1
505280	Lithium ion (Pouch)	2400	4.2	1
525680	Lithium ion (Pouch)	1500	4.2	1
534860	Lithium ion (Pouch)	1000	4.2	1
545288	Lithium ion (Pouch)	1500	4.2	1
5465120	Lithium ion (Pouch)	2750	4.2	1
575995	Lithium ion (Pouch)	5000	4.35	1
604050	Lithium ion (Pouch)	750	4.2	1
625280	Lithium ion (Pouch)	1500	4.2	1
633960	Lithium ion (Pouch)	875	4.2	1
636083	Lithium ion (Pouch)	2000	4.2	1
683086	(Pouch)	2000	4.2	1
695268	Lithium ion (Pouch)	1500	4.2	1
724556	Lithium ion (Pouch)	1000	4.2	1
755796	Lithium ion (Pouch)	5000	4.2	1
764269	Lithium ion	2550	4.25	4
794269	Lithium ion (Pouch)	3000	4.2	1
795590	Lithium ion (Pouch)	2500	4.2	1
882543	Lithium ion (Pouch)	500	4.2	1
903558	Lithium ion (Pouch)	2000	4.2	1
904050	Lithium ion (Pouch)	2000	4.2	1
955680	Lithium ion (Pouch)	2500	4.2	1
DPC-3032100	Lithium ion	850	4.25	4
DPC-35108148	Lithium ion (Pouch)	5800	4.25	1
DPC-35113140	Lithium ion (Pouch)	6000	4.25	1
DPC-3632100	Lithium ion	1200	4.25	4
DPC-3876111	Lithium ion (Pouch)	3000	4.25	1
DPC-40111125	Lithium ion (Pouch)	5600	4.25	1
DPC-403500				

	Lithium ion (Pouch)	2900	4.25	1
DPC-417596	Lithium ion (Pouch)	3000	4.25	1
DPC-4570112	Lithium ion (Pouch)	3800	4.25	1
DPC-458090	Lithium ion	3200	4.25	2, 4
DPC-459595	Lithium ion (Pouch)	4000	4.25	1
DPC-5252100	Lithium ion	2200	4.25	2, 4
DPC-5528128	Lithium ion	1400	4.25	2, 4
DPC-565583	Lithium ion (Pouch)	2400	4.25	1
DPC-603193A	Lithium ion	950	4.25	4
DPC-603193B	Lithium ion	1200	4.25	4
DPC-603443	Lithium ion	800	4.25	4
DPC-6064100	Lithium ion (Pouch)	1100	4.25	1
DPC-6332100	Lithium ion	1400	4.25	2, 4
DPC-644658	Lithium ion (Pouch)	1600	4.25	1
DPC-6540105	Lithium ion	1800	4.25	2, 4
DPC-6540110	Lithium ion	2200	4.25	2, 4
DPC-702994	Lithium ion	1400	4.25	2, 4
DPC-703196	Lithium ion	1600	4.25	2, 4
DPC-715062	Lithium ion (Pouch)	1800	4.25	1
DPC-733063	Lithium ion	1000	4.25	4
DPC-786080	Lithium ion (Pouch)	850	4.25	1
DPC-80100110	Lithium ion (Pouch)	2600	4.25	1
DPC-805053	Lithium ion	1600	4.25	2, 4
DPC-8065103	Lithium ion (Pouch)	2200	4.25	1

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test
- 3 - Complies with all single-cell tests except the projectile test
- 4 - Complies with all single-cell tests except the crush test

Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.
Last Updated on 2015-09-18

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".