

**IMPROVED CERTIFICATIONS
SEARCH TOOL. REGISTER NOW!****LEARN MORE****BBCV2.MH60676
Lithium Batteries - Component**If you notice a change to your BBCV2 Listing Card, click [here](#) to learn more.[Page Bottom](#)**Lithium Batteries - Component**[See General Information for Lithium Batteries - Component](#)**DONGGUAN NOVEL BATTERY TECHNOLOGY CO LTD**

MH60676

Bldg A4, A5 Fengfa Industrial Area
Zhenxing Rd, Wulian Village
Fenggang Town
Dongguan, Guangdong 523000 CHINA

Model No.	Secondary Type ^[d]	Max Charging Current (Ic), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]
125050	Lithium ion (Pouch)	3200	4.25	2
2765140	Lithium ion (Pouch)	3000	4.25	2
2774180	Lithium ion (Pouch)	4600	4.25	2
30100140	Lithium ion (Pouch)	5000	4.25	2
3282122	Lithium ion (Pouch)	3325	4.35	2
3378107	Lithium ion (Pouch)	2800	4.35	2
3482133	Lithium ion (Pouch)	3500	4.35	2
40110175	Lithium ion (Pouch)	6300	4.35	2
452540	Lithium ion (Pouch)	480	4.25	2
502530	Lithium ion (Pouch)	300	4.25	2
503035	Lithium ion (Pouch)	500	4.25	2
5450116	Lithium ion (Pouch)	4000	4.25	2
5565110	Lithium ion (Pouch)	5000	4.25	2
603038	Lithium ion (Pouch)	680	4.25	2
603450	Lithium ion (Pouch)	1200	4.25	2
NV284155P	Lithium ion (Pouch)	350	4.2	2
NV29100145P	Lithium ion (Pouch)	2250	4.2	2
NV30102110P	Lithium ion (Pouch)	2000	4.2	2
NV33100105P	Lithium ion (Pouch)	2100	4.2	2
NV336595P	Lithium ion (Pouch)	1300	4.2	2
NV3570125P	Lithium ion (Pouch)	1800	4.2	2
NV357090P	Lithium ion (Pouch)	1250	4.2	2
NV357095P	Lithium ion (Pouch)	1400	4.2	2

NV367095P	Lithium ion (Pouch)	1500	4.2	2
NV3853155P	Lithium ion (Pouch)	1900	4.2	2
NV3899164P	Lithium ion (Pouch)	3900	4.2	2
NV502030P	Lithium ion (Pouch)	125	4.2	2
NV603030P	Lithium ion (Pouch)	260	4.2	2
NV623450P	Lithium ion (Pouch)	525	4.2	2
NV623463P	Lithium ion (Pouch)	750	4.2	2
NV783048P	Lithium ion (Pouch)	575	4.2	2


[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test
- 3 - Complies with all single-cell tests except the projectile test
- 4 - Complies with all single-cell tests except the crush test



Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.
Last Updated on 2017-11-30

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".